



# Voice Control

by



Apart from graphical menus and controls, voice control has been identified as a desirable interaction modality for the ImAc player, especially with the availability of home 'smart speakers'.

#### **Features**

## **Advantages**

- The user can control the player without opening the menu, or removing a head mounted display to find a physical button.
- It is easy to use and learn and allows the user to talk to the player with natural language.
- Provides responses through the smart speaker, not through the player, separating the control from the media.
- Many users are already using and familiar with smart speakers for control.
- The ImAc remote gateway can be easily extended to support new devices as they become available.

#### How it is works


 A unique identifier is used to specify each each smart speaker or remote controller, usually its serial number.

General Settings

( Menu Type

Voice Control

- When voice control is enabled in the player, the device identifier is specified and the player opens a WebSocket to the gateway with this identifier.
- The gateway listens for requests from any smart speakers and controllers, and forwards the requests to any connected players registered with the same identifier.





command.





5. ImAc Player - The player responds to the command.



4. **Gateway** - The gateway receives the request and the device identifier that sent it. Any connected players that are registered with the identifier are forwarded the









## **ImAc Gateway**

#### The Gateway Server


- The gateway is a Node.js server which manages all of the communication between voice control devices and the player.
- •There are three types of 'device', which can connect to the gateway:
- 1. Controllers Any device which issues commands
- 2.Players Any device which consumes commands
- 3.Monitors Any device which consumes all communications for testing and monitoring
- For example: If you have a player with the ID 'USAL' it will receive commands from a controller with the ID 'USAL' but not from a controller with the ID 'I2CAT'.

#### The Gateway Monitor:

- The gateway-monitor page contains three sections as below:
- 'Currently connected devices', shows all of the connections to the gateway. The gateway-gateway-monitor page will appear in the list of devices as a monitor, and you can then see each of the connected players, controllers and other monitor pages that are currently open.
- 'Latest Activity' shows the every activity that the server has performed since you opened the page. This includes devices connecting and disconnecting as well as commands being sent.
- 'Links' gives two html links to other pages on the server, which replicates a controller and a player. Opening either of these will ask for the user to type in a device ID, and then replicate either a controller or a player.

# **Currently connected devices:**

Socket Id	Device ID	Туре	Description	Client Address	Connected Since
JxTPg8NPt7UnqJ_EAAGv	USAL_TEST	control	WebControl	::ffff:146.87.136.63	5/28/2019, 11:11:44 AM
JJYjBqTX-6uTXjywAAGu	ImAc	monitor	Monitor	::ffff:146.87.136.63	5/28/2019, 11:08:06 AM
Q29qYfAtl9oO-kXvAAFs	USAL_TEST	player	WebPlayer	::ffff:146.87.113.21	5/23/2019, 11:06:30 PM



# **Latest Activity:**

Timestamp	Activity		
28/05/2019, 10:11:47	[JxTPg8NPt7UnqJ_EAAGv] control added with id: "USAL_TEST"		
28/05/2019, 10:08:09	[JJYjBqTX-6uTXjywAAGu] monitor added with id: "ImAc"		

## Links:

Controller Player

#### **Further Details**

Contact: c.j.hughes@salford.ac.uk






















**Example Intent Path (Spanish)** 

